

WHA-206TB
HEADPHONE AMPLIFIER / COMBO


WHA-204TB HEADPHONE AMP.

방송 스튜디오에서 진행자 및 출연자가 방송 프로그램을 모니터링하기 위한 헤드폰 앰프로서, 6개의 헤드폰 사용이 가능하며, 별도의 폰박스 6개를 추가로 연결할 수 있다. 또한 Announcer Cough Box 기능이 부가되어 있어 진행자는 조정실과 통화가 가능하다. Analog와 Digital 오디오 겸용으로 설계되었고, 헤드폰과 이어폰 사용을 모두 지원한다.



WHA-204TB Rear View (Remove Cover)



WHA-206B PHONE BOX

Features
[Headphone Amplifier]

- ◆ Desk Type
- ◆ Digital Audio(AES/EBU) Input (PGM)
- ◆ Analog Audio Input (PGM, Stereo)
- ◆ Digital/Analog PGM Select
- ◆ Mono/Stereo Mode Select
- ◆ Input Level Attenuator(0dB/-20dB)
- ◆ 10 Dot Stereo Level Meter (VU)
- ◆ 채널(MC1~2 & Guest1~4) 별 H/P Volume
- ◆ 6.35mm & 3.5mm Phone Jack
- ◆ Phone Box(6CH) 확장 가능

[Announcer Cough Box]

- ◆ On Air & Call Lamp
- ◆ Mic Mute Switch & Tally Output
- ◆ Talk Switch & Mic
- ◆ MC.1 & MC.2 Headphone 사용
- ◆ Analog Audio Input/Output (Talk)

Ordering Information

- ✓ WHA-202TB 2CH + 4CH
- ✓ WHA-206D+206B 2CH + 5CH ~ 10CH

Technical Specification
Analog Input (PGM)

Channel 2CH (Left & Right)
 Impedance High (Balanced)
 Level +4dBu (nominal)

Digital Input (PGM)

Format AES/EBU
 Impedance 110Ω (Balanced)
 Sampling Rate Auto (32~96KHz)
 Audio Level -20dBFS (nominal)

Input Control

Select Digital/Analog
 Mode Mono/Stereo

Level Meter

Type LED Bar Graph Meter
 Resolution 10 Dot, Stereo

Headphone Output

Channel 6CH (WHA-206D)
 7~12CH (WHA-206TB+206B)
 Freq. Response ±0.5dB (20Hz~20KHz)
 Distortion ≤0.2% (20Hz~20KHz)
 S/N Ratio ≥80dB
 Connector 6.35mm & 3.5mm Phone Jack

Tally Control

Input On Air, Call, Talk
 Output Mute, Talk

General

Power AC 100~220V 50/60Hz
 Dimensions 240(W)x320(H)x50(D)mm (206TD)
 80/100(W)x34(H)x120(D)mm (206B)