

**WTB-105AN**
**ANNOUNCER COUGH BOX**


WTB-105AN ANNOUNCER COUGH BOX

Talkback Amplifier(WTB-105E)나 Audio Mixer와 연결하여 사용하는 Studio용 Cough Box로서 내장된 고감도 Mic와 Headphone을 이용하여 조정실과의 통화기능을 수행한다. 또한 On Air Lamp와 Call Lamp, Talk SW, Mic Mute SW 등이 수용되어 있어 원활한 방송진행을 도와준다. 개별 음량조절이 가능한 2개의 Headphone 단자가 있어 2명의 MC가 각각 사용할 수 있으며, Level Meter(Stereo)가 있어 방송(신호) 상태를 시각적으로 확인이 가능하다.



WTB-105AN Rear View

**Features**

- ◆ Desk Type
- ◆ On Air & Call Lamp
- ◆ Mic Mute Switch & Tally Output
- ◆ Talk Switch & Mic
- ◆ MC.1 & MC.2 Headphone 사용
- ◆ 6.35mm & 3.5mm Phone Jack
- ◆ 채널(MC1~2) 별 H/P Volume
- ◆ Talk Signal Input/Output (Analog)
- ◆ WTB-105A 호환 (Dsub-25 커넥터)
- ◆ PGM Signal Input (Analog, Stereo)
- ◆ Stereo/Mono Select
- ◆ 10 Dot Stereo Level Meter (VU)
- ◆ PGM Monitoring을 위한 Phone Box(Guest용)

**Ordering Information**

- ✓ WTB-105AN                      Main
- ✓ WHA-206B                      Phone Box , 1CH~6CH

**Technical Specification**
**Analog Input (PGM)**

Channel                      2CH (Left & Right)  
 Impedance                  High (Balanced)  
 Level                          +4dBu (nominal)

**Receive Input (Talkback)**

Impedance                  High (Balanced)  
 Level                          +4dBu (nominal)

**Send Output (Talkback)**

Impedance                  Low (Balanced)  
 Level                          +4dBu (nominal)

**Control I/O**

Tally Input                      On Air, Call, Talk  
 Tally Output                    Talk, Mute  
 DC Output                      Mute(+12V)  
 Device                          Photocoupler

**Headphone Output**

Channel                      2CH (Stereo)  
 Freq. Response               ±0.5dB (20Hz~20KHz)  
 Distortion                    ≤0.2% (20Hz~20KHz)  
 S/N Ratio                      ≥80dB  
 Connector                      6.35mm & 3.5mm Phone Jack

**Level Meter**

Type                              LED Bar Graph Meter  
 Resolution                      10 Dot, Stereo

**General**

Power                            DC 12V  
 Dimensions                    240(W)x254(H)x50(D)mm